CERTIFICATE OF COMPLIANCE

Certificate Number E108780

Report Reference E108780 – 20030218

Issue Date 2020-APRIL-18

Issued to: LS ELECTRIC Co Ltd

95 Baekbong-ro Heungdeok-gu Cheongju-si

Chungcheongbuk-do 28439 KOREA

This certificate confirms that MOTOR CONTROLLERS, MAGNETIC

representative samples of See next page for Models

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1 AND CAN/CSA C22.2 No. 60947-1-13, Low-

Voltage Switchgear and Controlgear

UL 60947-4-1 and CSA C22.2 NO 60947-4-1-14, Low-Voltage Switchgear and Controlgear - Part 4-1: Contactors and motor-starters - Electromechanical contactors and

motor-starters

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutui/locations/



CERTIFICATE OF COMPLIANCE

Certificate Number

E108780

Report Reference

E108780 - 20030218

Issue Date

2020-APRIL-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

PRODUCT COVERED:

USL, CNL Across-the-line reversing starters are designated: GMS-6MR, -9MR, and -12MR, may be followed by /3, /K, D/3, or D/K.

Magnetic motor controllers are designated: GMC-, GMD or GMC(D) may be followed by -6M, -9M, -12M, may be followed by F, P or C.

Reversing magnetic contactors are designated: GMC or GMD or GMC(D) may be followed by -6MR, -9MR, and -12MR.

4-Pole magnetic contractors, Models GMC or GMD or GMC(D) may be followed by 6M, 9M, -12M, followed by /4.

4-Pole reversing magnetic contractors are designated: GMC or GMD or GMC(D) may be followed by 6MR, 9MR, and 12MR, followed by /4.

Accessories for GMC-#M magnetic motor controllers, Delay Timer Model AT-12M. Surge Suppressor model AS-12M.

Accessories for GMC(D)-6M, -9M, -12M, Mechanical interlock units, Type AR Series, AR-12M.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

