

CONSTRUCTION DETAILS:

Marking - Device is marked on adhesive-backed label, designated: Listee's name, file number, or trademarks, Type number and electrical ratings.

"60/75°C, Cu wire only", or equivalent.

"Terminal Torque __ in.-lbs (see Ratings)", or equivalent.
Torque marking may be provided loose with the equipment.

"Suitable For Use On A Circuit Capable Delivering Not More Than rms Symmetrical Amperes, Volts Maximum. When Protected by Class Fuses.", or equivalent.

The following Trademarks may be used:



Alternate Trademark



File E206826
Project 99SC48292

December 08, 1999

REPORT
ON
AUXILIARY DEVICES

LG Industrial Systems Co. Ltd.
Chung Cheong Bug-Do, Korea

Copyright © 1999 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above named company to reproduce this Report provided it is reproduced in its entirety.

DESCRIPTION

PRODUCT COVERED:

USL and CNL - Auxiliary Contactors, Series GMR, followed by -4, -6, or -8, may be followed by D.

Accessories - Auxiliary Contact Block, AU-2 and AU-4.

GENERAL:

These devices are open type auxiliary contact assemblies intended for rail or screw down type mounting.

The AU-2 and AU-4 are intended for mounting atop the auxiliary contactors, GMR series. They connect directly to the plunger of the contactor, opening and/or closing the auxiliary contacts when the plunger is pulled in by the coil.

RATINGS:

A600, P600

Coil Voltage - 24 - 550 V ac @ 50 Hz
24 - 600 V ac @ 60 Hz
12 - 250 V dc (GMR- ()D Series only)

NOMENCLATURE:

GMR - 4 D
I II III

I. Series Designation

II. Number of Contacts - 4: 4 Contacts
6: 6 Contacts, used w/AU-2
8: 8 Contacts, used w/AU-4

III. Coil Voltage -

Blank: AC Coil
D: DC Coil